

SINED Stainless steel AISI 316L : C-box fixing system

USER MANUAL



DOCCIA-C-BOX

SINED C-BOX, how to safely position and install a stainless steel outdoor shower. How to make a shower stable in just a few steps.

Included in the SINED stainless steel shower package is the complete fixing kit. The unique C-box system allows you to securely fix your shower, connecting it directly to hot and cold water at home. Everything is very simple. Below are the package components.



The special feature of this shower model is the unique C-box fixing system.



The C-Box enables perfect installation and is protected by a lockable cover to be used when the shower is dismantled. The C-Box must be installed perfectly level and fixed to the floor (on concrete) with 4 metal dowels, supplied.



Inside the C-Box is the quick coupling for connecting the stainless steel shower.

The quick couplings located on the shower tray are connected with a watertight three-OR system



The shower is attached to the C-Box with screws, the drawing below will explain step by step

① Confirm positions for embedded C-box and shower place (distance btw them is 750mm), then dig holes based on C-box size.

vertical to shower place
for cold water
for hot water
shower place

② Connect hot and cold water pipes to the embedded C-box, make sure no leaking.

4pcs MS*80 expansion screws
145*145mm

③

middle line
Bottom line

Make sure C-box is vertical and centered to you. Tighten up C-box to hole bottom with 4pcs MS expansion screws, make sure floor tile must be higher than bottom line and lower than middle line of C-box.

④ Throw out C-box cover and plugs for hot and cold water outlets. Cut the extra top part of C-box.

8mm 6-angle tool

⑤ Insert lower pipe to the C-box, connect bottom plate to C-box with 4 screws, then push down the bottom decorated cover to floor.

hot water
cold water
5mm 6-angle tool

Outdoor Shower simple installation manual for Hot and Cold Water with embedded C-box

⑥ Insert upper pipe into the lower pipe, match back lines on two pipes together to get installation done, and lock screw in back pipes to get installation done.
Connect handshower with flexible hose if have. (if items have spout, pls note we already got it installed.)

2.5mm 6-angle tool
750

WARNINGS

Please read the instructions carefully before installing and using your shower.

This manual contains important information for the correct use and maintenance of your shower and should be kept for future reference.

1) Warranty

SINED showers are guaranteed for 2 years from the date of purchase against defects in materials and workmanship.

- Excluded from the guarantee are components subject to wear and tear including mixers, shower heads, taps, etc.
- Damage due to incorrect assembly, improper use and incorrect maintenance (e.g. use of inappropriate cleaning agents) are not covered by the warranty.
- Damage resulting from the use of non-original spare parts is not covered by the guarantee.
- Damage resulting from work not carried out by specialist technicians is not covered by the warranty.
- Damage due to frost, limescale or other impurities inside the shower is not covered by the guarantee.

In the event of problems covered by the guarantee, the product must be returned to the seller.

- The product shall be carefully packed and complete with all parts and accessories;
- The reason for return must be described in detail and proof of purchase (invoice or receipt) must be provided;
- The return shipping costs shall be borne by the purchaser;
- The returned product will be inspected at the seller's premises and repaired or replaced at the seller's sole discretion.

Manufacturing: M8 IMP & EXP CO., LTD

Address: No 5, Longxi Industrial Area

Yuhuan, Zhejiang, CHINA

Made in China Imported into Italy by M.P.C. srl Via Tortona 21 Milano 20144 Italy Tel
+39 02 21117815 e-mail info@mpcshop.it website www.sinedtechnology.com

The SINED trademark and the SINED logo are registered by SINED VENTAS ONLINE
S.L.U. EUTM 018196373